



ARPRO[®] Product Listing

Expanded Polypropylene (EPP) Low Utility Grade¹

BULK DENSITY SPECIFICATION

Black

Product Type	Density, grams/liter (g/l)		
	Lower Limit	Nominal	Upper Limit

5312	12.8	14.4	15.8
5313	14.4	16.2	18.0
5315	18.0	20.0	22.0
5317	21.0	23.0	25.0
5319	23.5	26.1	28.7
5325	26.0	29.0	32.0
5327	31.0	34.0	37.0
5328	32.5	35.3	38.1
5329	35.0	38.0	41.0
5330	38.4	41.7	45.0
5335	41.0	45.0	49.0
5337	44.3	48.1	52.0

White

Product Type	Density, grams/liter (g/l)		
	Lower Limit	Nominal	Upper Limit

3312	12.8	14.4	15.8
3313	14.4	16.2	18.0
3315	18.0	20.0	22.0
3317	21.0	23.0	25.0
3319	23.5	26.1	28.7
3325	26.0	29.0	32.0
3327	31.0	34.0	37.0
3328	32.5	35.3	38.1
3329	35.0	38.0	41.0
3330	38.4	41.7	45.0
3335	41.0	45.0	49.0
3337	44.3	48.1	52.0

¹Notes: Certain product grades may be limited to specific JSP Plant locations. Contact JSP for details.

ARPRO[®] LU-EPP 53XX/33XX Low Utility Series is a more resilient EPP product. While it is slightly less stiff vs. standard ARPRO[®] EPP, it produces a more flexible molded product with improved tensile elongation and tear strength. It can be molded using reduced utilities (lower steam pressures = less energy) vs. standard ARPRO EPP. Reduced utilities allow for the possibility of faster cycle times and faster processing times. This product is recommended for applications such as fabricated Plank or Block, and lower density EPP parts that require improved flexibility, resiliency, and tensile elongation properties.

