



ARPRO[®] Product Listing Expanded Polypropylene (EPP) High Density Grade¹

BULK DENSITY SPECIFICATION

<u>Black</u>

Product Type	Density, grams/liter (g/l)		
	Lower Limit	Nominal	Upper Limit
5470	83.0	90.2	97.4
5473	86.3	93.8	101.3
5475	88.3	96.0	103.7
5480	93.7	101.8	109.9
5483	96.5	104.9	113.3
5485	101.8	110.7	119.6
5490	107.3	116.6	125.9
5495	115.4	125.4	135.4
5497	131.7	143.2	154.7
5498	142.6	155.0	167.4
5499	165.6	180.0	194.4
5499HD	184.0	200.0	216.0
5499UHD	202.4	220.0	237.6

¹Note: Certain product grades may be limited to specific JSP Plant locations. Contact JSP for details.

ARPRO® is a registered trademark of JSP International Group, Ltd. PUBLICATION: techdoc_HighDensityGradeList_ARPRO-EPP_2018



The information contained herein is based upon the results of limited laboratory tests on test samples of numerical model from expanded polyclefin resin manufactured by JSP. There can be no assurance that the similar results will be achieved in simulated tests or actual use of commercial product moled by customers of JSP. Product performance may vary substantially depending upon the particular application or processing involved. The listed properties are illustrative only and not the product specifications. All suggestions and recommendations are made without variantly since the conditions of use are beyond JSP's control. Processing and applications of JSP foram products can influence molded part performance in many ways. Consessors and/or users are advised that here may be a need to conduct independent tests and experiments in order for them to determine the extent to which they may choose to rely upon such information in their business operations. JSP disclaims any liablik' in connection with the use of the information and does not warrant adams infinionement to reasons of the two forducts in conducts in order material or in any orocess.